

Order Code: XCBHWPSWOM3HFS

16W - Square Bulkhead with Opal diffuser - IP65 - 3hrs Maintained Emergency - 4000K - White Base - Microwave Sensor



Features

- Suitable for general interior or exterior use
• 20mm conduit side cable entries for wall or ceiling fix
• Up to 94 lumens per watt efficacy

Construction

- Polycarbonate body
• White base or black base available
• High quality polycarbonate construction
• Opal or prismatic diffuser available
• Integral emergency option available
• Supplied as standard with neutral white [4000K] LED



Technical Data

Table with 2 main sections: General and Electrical. General includes Luminaire Wattage (16W), Weight (1.22kg), Operating Temperature (5 to 25°C), Light Output (1500 lumens, 94 lm/W), LED (4000K CCT, 80 CRI, 4 Macadam Elipses), and Emergency (210 lumen operating, 2W). Electrical includes Rated Input Current (0.07A), Power Factor (0.85), Input Voltage Range (220-240V), Inrush Current Peak (10A), Surge Protection (1kV), Conductor Size (2.5mm), and Terminal Type (4 pole screw down).

**Order Code:** XCBHWPSWOM3HFS

16W - Square Bulkhead with Opal diffuser - IP65 - 3hrs Maintained Emergency - 4000K - White Base - Microwave Sensor

Dimensions

|        |     |
|--------|-----|
| A (mm) | 256 |
| B (mm) | 256 |
| C (mm) | 91  |

Line Drawing

