# xcite LED Lighting

## **Data Sheet**



### Order Code: XCBHWPSWOM3HFS

16W - Square Bulkhead with Opal diffuser - IP65 - 3hrs Maintained Emergency - 4000K - White Base - Microwave Sensor

### **Features**



- Suitable for general interior or exterior use
- 20mm conduit side cable entries for wall or ceiling fix
- Up to 94 lumens per watt efficacy

#### Construction

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED

















### **Technical Data**

General		
Luminaire Wattage (W)	16	F
Weight (kg)	1 22	F
Operating Temperature (ta °C)		I
Light Output		
Lumens (lm)	1500	
Efficacy (lm/W)	0.4	
LED		
CCT (K)	4000	
CRI	80	
Macadam Elipses	4	
Emergency		
Emergency Lumen Operating	210	
Emergency Wattage (W)	2	

Electrical		
Rated Input Current (A)	0.07	
Power Factor (pf)	0.85	
Input Voltage Range (VAC)	220-240	
Inrush Current Peak (A)	10	
Surge Protection (kV)	1	
Conductor Size (mm)	2.5	
Terminal Type	4 pole screw down	

# xcite LED Lighting

## **Data Sheet**



### Order Code: XCBHWPSWOM3HFS

16W - Square Bulkhead with Opal diffuser - IP65 - 3hrs Maintained Emergency - 4000K - White Base - Microwave Sensor

#### **Dimensions**

A (mm)	256
B (mm)	256
C (mm)	91

### Line Drawing



