# xcite LED Lighting

### **Data Sheet**



Order Code: XCBHWPSWP

16W - Square Bulkhead with Prismatic diffuser - IP65 - 4000K - White Base



### **Features**

- Suitable for general interior or exterior use
- 20mm conduit side cable entries for wall or ceiling fix
- Up to 113 lumens per watt efficacy

#### Construction

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED

















### **Technical Data**

General		
Luminaire Wattage (W)	16	Rated Input C
Weight (kg)	0.86	Power Factor
Operating Temperature (ta °C)	0 to 25	Input Voltage
Light Output		Inrush Curren
Lumens (lm)	1800	Surge Protect
Efficacy (lm/W)	113	Conductor Siz
LED		Terminal Type
CCT (K)	4000	
CRI	80	
Macadam Elipses	4	
Driver		
Driver Current (mA)	240	
Forward Voltage (V)	54-64	

Electrical	
Rated Input Current (A)	0.07
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	10
Surge Protection (kV)	1
Conductor Size (mm)	2.5
Terminal Type	3 pole piano key

# xcite LED Lighting

## **Data Sheet**



### Order Code: XCBHWPSWP

16W - Square Bulkhead with Prismatic diffuser - IP65 - 4000K - White Base

### **Dimensions**

A (mm)	256
B (mm)	256
C (mm)	93

### Line Drawing



