xcite LED Lighting

Data Sheet



Order Code: XCBHWPSWPM3HFS

16W - Square Bulkhead with Prismatic diffuser - IP65 - 3hrs Maintained Emergency - 4000K - White Base - Microwave Sensor **Features**



- Suitable for general interior or exterior use
- 20mm conduit side cable entries for wall or ceiling fix
- Up to 113 lumens per watt efficacy

Construction

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED

















Technical Data

recimical Data			
General			Elec
Luminaire Wattage (W)	16	Rated Input Current (A)	
Weight (kg)	1.22	Power Factor (pf)	
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	
	Inrush Current Peak (A)		
Light Output Lumens (lm)	Light Output umens (lm) 1800	Surge Protection (kV)	
	113	Conductor Size (mm)	
Efficacy (Im/W)		Terminal Type	
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		
Emergency			
Emergency Lumen Operating	236		
Emergency Wattage (W)	2		

Electrical		
Rated Input Current (A)	0.07	
Power Factor (pf)	0.85	
Input Voltage Range (VAC)	220-240	
Inrush Current Peak (A)	10	
Surge Protection (kV)	1	
Conductor Size (mm)	2.5	
Terminal Type	4 pole screw down	

xcite LED Lighting

Data Sheet



Order Code: XCBHWPSWPM3HFS

16W - Square Bulkhead with Prismatic diffuser - IP65 - 3hrs Maintained Emergency - 4000K - White Base - Microwave Sensor

Dimensions

A (mm)	256
B (mm)	256
C (mm)	91

Line Drawing



