

**Order Code: XCBLAM3STEU3**

XCITE BLADE ST XCBLA 2W - 6500K - Fixed output - Emergency Self-test



**Features**

- Ideal for retrofit of existing emergency fixtures
- Suitable for ceiling, wall or surface fixings
- 20mm conduit rear cable entries
- Supplied with flag pole mounting kit
- Multi purpose LED emergency drop light
- Supplied with LiFePO4 battery

**Construction**

- Operates in maintained and non-maintained mode
- Supplied with EURO 4 running man legend
- Integral auto self-test for reduced maintenance, includes a disable function



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	2	Rated Input Current (A)	0.04
Weight (kg)	0.79	Power Factor (pf)	0.2
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
		Conductor Size (mm)	1.5
		Terminal Type	4 pole screw down
Driver			
Driver Current (mA)	135		
Forward Voltage (V)	2.64		

**Order Code:** XCBLAM3STEU3

XCITE BLADE ST XCBLA 2W - 6500K - Fixed output - Emergency Self-test

### Dimensions

A (mm)	344
B (mm)	237
C (mm)	42