xcite LED Lighting

Data Sheet



Order Code: XCBLC15CT

15W - Downlight BL CC - CCTK Selector [3000K/4000K/6000K]- Fixed output



Features

- Suitable for general domestic and commercial use
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- · Available in 6 sizes
- Available in 6 different outputs
- Phase cut dimming option available
- 3 hours emergency maintained with compatible conversion box Emergency Kit
- Up to 100 lumens per watt efficacy

Construction

• Frosted polycarbonate diffuser















Technical Data

General		
Luminaire Wattage (W)	15	F
Weight (kg)	0.26	F
	0 to 25	I
Light Output		
Lumens (lm)	1500	
Efficacy (lm/W)	100	
LED		
CCT (K)	TRI-COLOUR	
CRI	80	
Macadam Elipses	4	
Driver		
Driver Current (mA)	400	
Forward Voltage (V)	22.50	

Electrical		
Rated Input Current (A)	0.7	
Power Factor (pf)	0.96	
Input Voltage Range (VAC)	198-264	
Inrush Current Peak (A)	2.1	
Surge Protection (kV)	1	
Conductor Size (mm)	0.75 - 1.5 mm²	
Terminal Type	PUSH BUTTON 2	



xcite LED Lighting

Data Sheet



Order Code: XCBLC15CT

15W - Downlight BL CC - CCTK Selector [3000K/4000K/6000K]- Fixed output

Dimensions

C (mm)	26
Cut Out (mm)	180
Dia. (mm)	200

Line Drawing



