# xcite LED Lighting

## **Data Sheet**



Order Code: XCBLC22CTD

22W - Downlight BL CC - CCTK Selector [3000K/4000K/6000K]- Dimmable



### **Features**

- Suitable for general domestic and commercial use
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- · Available in 6 sizes
- Available in 6 different outputs
- Phase cut dimming option available
- 3 hours emergency maintained with compatible conversion box Emergency Kit
- Up to 114 lumens per watt efficacy

#### Construction

• Frosted polycarbonate diffuser















## **Technical Data**

General		
Luminaire Wattage (W)	22	Rated Input Curre
Weight (kg)	0.40	Power Factor (pf)
Operating Temperature (ta °C)	0 to 25	Input Voltage Ra
Light Output		Inrush Current Pe
Lumens (Im)	2500	
Efficacy (lm/W)	114	Conductor Size (
LED		Terminal Type
CCT (K)	TRI-COLOUR	
CRI	80	
Macadam Elipses	4	
Driver		
Driver Current (mA)	550	
Forward Voltage (V)	25-38	

Electrical		
Rated Input Current (A)	0.11	
Power Factor (pf)	0.96	
Input Voltage Range (VAC)	198-264	
Inrush Current Peak (A)	2.06	
Surge Protection (kV)	1	
Conductor Size (mm)	0.75 - 1.5 mm²	
Terminal Type	PUSH BUTTON 2	

# xcite LED Lighting

# **Data Sheet**



Order Code: XCBLC22CTD

22W - Downlight BL CC - CCTK Selector [3000K/4000K/6000K]- Dimmable

### **Dimensions**

C (mm)	26
Cut Out (mm)	280
Dia. (mm)	300

## Line Drawing



