

Order Code: XCBLC8CTD

8W - Downlight BL CC - CCTK Selector [3000K/4000K/6000K]- Dimmable



Features

- Suitable for general domestic and commercial use
- CCT adjustable via 3-way selector switch [3000K/4000K/6000K]
- Available in 6 sizes
- Available in 6 different outputs
- Phase cut dimming option available
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 88 lumens per watt efficacy

Construction

- Frosted polycarbonate diffuser



Technical Data

| General | | Electrical | |
|-------------------------------|-------------------|---------------------------|----------------------------|
| Luminaire Wattage (W) | 8 | Rated Input Current (A) | 0.04 |
| Weight (kg) | 0.12 | Power Factor (pf) | 0.96 |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 198-264 |
| Light Output | | Inrush Current Peak (A) | 1 |
| Lumens (lm) | 700 | Surge Protection (kV) | 1 |
| Efficacy (lm/W) | 88 | Conductor Size (mm) | 0.75 - 1.5 mm ² |
| LED | | Terminal Type | PUSH BUTTON 2 |
| CCT (K) | 3000K/4000K/6000K | | |
| CRI | 80 | | |
| Macadam Elipses | 4 | | |
| Driver | | | |
| Driver Current (mA) | 200 | | |
| Forward Voltage (V) | 27-42 | | |

Order Code: XCBLC8CTD

8W - Downlight BL CC - CCTK Selector [3000K/4000K/6000K]- Dimmable

Dimensions

| | |
|--------------|-----|
| C (mm) | 26 |
| Cut Out (mm) | 100 |
| Dia. (mm) | 120 |

Line Drawing

