

Order Code: XCBLP12650CW
50W - Recessed Backlit Panel - 1200mm x 600mm - 5000K



- Features
• Ideal for retrofit of existing T5 or T8 fixtures
• Suitable for offices and schools
• Backlit recessed module
• More consistent and uniform appearance than traditional edge-lit panels or downlights
• Compatible with Panel Frame and Surface Panel Frame
• 3 hours emergency maintained with compatible conversion box Emergency Kit
• Up to 106 lumens per watt efficacy

- Construction
• Extruded aluminium frame
• High performance opal TP[b] diffuser
• Plug and play driver
• Supplied in warm white [3000K], neutral white [4000K], cool white [5000K] or daylight [6000K]
• Please note daylight [6000K] warm white [3000K] is only available in 600mm x 600mm

Technical Data

Table with 2 main sections: General and Electrical. General includes Luminaire Wattage, Weight, Operating Temperature, Light Output (Lumens, Efficacy), LED (CCT, CRI, Macadam Elipses), and Driver (Driver Current, Forward Voltage). Electrical includes Rated Input Current, Power Factor, Input Voltage Range, Inrush Current Peak, Surge Protection, Conductor Size, and Terminal Type.

Order Code: XCBLP12650CW
50W - Recessed Backlit Panel - 1200mm x 600mm - 5000K

Dimensions

A (mm)	1195
B (mm)	595
C (mm)	35

Line Drawing

