

Order Code: XCBLP6630CW
30W - Recessed Backlit Panel - 600mm x 600mm - 5000K



Features

- Ideal for retrofit of existing T5 or T8 fixtures
- Suitable for offices and schools
- Backlit recessed module
- Compatible with Panel Frame and Surface Panel Frame
- More consistent and uniform appearance than traditional edge-lit panels or downlights
- 3 hours emergency maintained with compatible conversion box Emergency Kit
- Up to 100 lumens per watt efficacy

Construction

- Extruded aluminium frame
- High performance opal TP[b] diffuser
- Plug and play driver
- Supplied in warm white [3000K], neutral white [4000K], cool white [5000K] or daylight [6000K]
- Please note daylight [6000K] warm white [3000K] is only available in 600mm x 600mm

Technical Data

General		Electrical	
Luminaire Wattage (W)	30	Rated Input Current (A)	0.13
Weight (kg)	1.64	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
Light Output		Inrush Current Peak (A)	14
Lumens (lm)	3000	Surge Protection (kV)	2
Efficacy (lm/W)	100	Conductor Size (mm)	1.5
LED		Terminal Type	2 pole grip wire
CCT (K)	5000		
CRI	80		
Macadam Elipses	4		
Driver			
Driver Current (mA)	750		
Forward Voltage (V)	27 to 42		

Order Code: XCBLP6630CW

30W - Recessed Backlit Panel - 600mm x 600mm - 5000K

Dimensions

A (mm)	595
B (mm)	595
C (mm)	35

Line Drawing

