## xcite LED Lighting

### **Data Sheet**

Order Code: XCBLP6630DL

30W - Recessed Backlit Panel - 600mm x 600mm - 6000K





- · Ideal for retrofit of existing T5 or T8 fixtures
- · Suitable for offices and schools
- Backlit recessed module
- Compatible with Panel Frame and Surface Panel Frame
- More consistent and uniform appearance than traditional edge-lit panels or downlights
- 3 hours emergency maintained with compatible conversion box **Emergency Kit**
- Up to 100 lumens per watt efficacy

#### Construction

- · Extruded aluminium frame
- High performance opal TP[b] diffuser
- · Plug and play driver
- Supplied in warm white [3000K], neutral white [4000K], cool white [5000K] or daylight [6000K]
- Please note daylight [6000K] warm white [3000K] is only available in 600mm x 600mm

























### **Technical Data**

		74. 2 4.ta	
General		Electrical	
Luminaire Wattage (W)	30	Rated Input Current (A)	0.13
Weight (kg)	1.85	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
Links Outrout		Inrush Current Peak (A)	14
Light Output  Lumens (Im)	3000	Surge Protection (kV)	2
Efficacy (lm/W)	100	Conductor Size (mm)	1.5
Lineacy (iiivv)		Terminal Type	2 pole grip wire
LED			
CCT (K)	6000		
CRI	80		
Macadam Elipses	4		
Driver			
Driver Current (mA)	750		
Forward Voltage (V)	27 to 42		

# xcite LED Lighting

### **Data Sheet**



Order Code: XCBLP6630DL

30W - Recessed Backlit Panel - 600mm x 600mm - 6000K

#### **Dimensions**

A (mm)	595
B (mm)	595
C (mm)	35

### Line Drawing





