xcite LED Lighting

Data Sheet



Order Code: XCBLP6630DLD

30W - Recessed Backlit Panel - 600mm x 600mm - 6000K





- · Ideal for retrofit of existing T5 or T8 fixtures
- Suitable for offices and schools
- Backlit recessed module
- More consistent and uniform appearance than traditional edge-lit panels or downlights
- Compatible with Panel Frame and Surface Panel Frame
- 3 hours emergency maintained with compatible conversion box **Emergency Kit**
- Up to 100 lumens per watt efficacy

Construction

- · Extruded aluminium frame
- High performance opal TP[b] diffuser
- · Plug and play driver
- Supplied in warm white [3000K], neutral white [4000K], cool white [5000K] or daylight [6000K]
- Please note daylight [6000K] warm white [3000K] is only available in 600mm x 600mm

























Technical Data

General		Electrical	
Luminaire Wattage (W)	30	Rated Input Current (A)	0.25
Weight (kg)	1.85	Power Factor (pf)	0.95
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
Linht Output		Inrush Current Peak (A)	40
Light Output Lumens (Im)	3000 100	Surge Protection (kV)	1
Efficacy (Im/W)		Conductor Size (mm)	1.5
Lineady (iiivv)		Terminal Type	2 pole grip wire
LED			
CCT (K)	6000		
CRI	80		
Macadam Elipses	4		
Driver			
Driver Current (mA)	750		
Forward Voltage (V)	24 to 42		

xcite LED Lighting

Data Sheet



Order Code: XCBLP6630DLD

30W - Recessed Backlit Panel - 600mm x 600mm - 6000K

Dimensions

A (mm)	595
B (mm)	595
C (mm)	35

Line Drawing





