## xcite LED Lighting

### **Data Sheet**



Order Code: XCBLP6630NWD

30W - Recessed Backlit Panel - 600mm x 600mm - 4000K





- · Ideal for retrofit of existing T5 or T8 fixtures
- · Suitable for offices and schools
- Backlit recessed module
- Compatible with Panel Frame and Surface Panel Frame
- More consistent and uniform appearance than traditional edge-lit panels or downlights
- 3 hours emergency maintained with compatible conversion box **Emergency Kit**
- Up to 100 lumens per watt efficacy

#### Construction

- · Extruded aluminium frame
- · High performance opal TP[b] diffuser
- · Plug and play driver
- Supplied in warm white [3000K], neutral white [4000K], cool white [5000K] or daylight [6000K]
- Please note daylight [6000K] warm white [3000K] is only available in 600mm x 600mm

























### **Technical Data**

Tooliniodi Data						
General		Electrical				
Luminaire Wattage (W)		30	Rated Input Current (A)	0.25		
Weight (kg)		1.64	Power Factor (pf)	0.95		
Operating Temperature (ta °C)		) to 25	Input Voltage Range (VAC)	220-240		
	:		Inrush Current Peak (A)	40		
· ·		3000	Surge Protection (kV)	1		
			Conductor Size (mm)	1.5		
			Terminal Type	2 pole grip wire		
	LED					
CCT (K)		4000				
CRI		80				
Macadam Elipses		4				
	Driver					
Driver Current (mA)		750				
Forward Voltage (V)	24	1 to 42				
Lumens (lm)  Efficacy (lm/W)  CCT (K)  CRI  Macadam Elipses  Driver Current (mA)	Driver	80 4 750	Surge Protection (kV) Conductor Size (mm)		1.5	

# xcite LED Lighting

## **Data Sheet**



### Order Code: XCBLP6630NWD

30W - Recessed Backlit Panel - 600mm x 600mm - 4000K

#### **Dimensions**

A (mm)	595
B (mm)	595
C (mm)	35

#### Line Drawing







