

Order Code: XCBLP6630NWD
30W - Recessed Backlit Panel - 600mm x 600mm - 4000K



Features

- Ideal for retrofit of existing T5 or T8 fixtures
- Suitable for offices and schools
- Backlit recessed module
- More consistent and uniform appearance than traditional edge-lit panels or downlights
- Compatible with Panel Frame and Surface Panel Frame
- 3 hours emergency maintained with compatible conversion box Emergency Kit
- Up to 100 lumens per watt efficacy

Construction

- Extruded aluminium frame
- High performance opal TP[b] diffuser
- Plug and play driver
- Supplied in warm white [3000K], neutral white [4000K], cool white [5000K] or daylight [6000K]
- Please note daylight [6000K] warm white [3000K] is only available in 600mm x 600mm

Technical Data

Table with 2 columns: Specification, Value. Rows include General (Luminaire Wattage, Weight, Operating Temperature), Light Output (Lumens, Efficacy), LED (CCT, CRI, Macadam Elipses), and Driver (Driver Current, Forward Voltage).

Table with 2 columns: Specification, Value. Rows include Electrical (Rated Input Current, Power Factor, Input Voltage Range, Inrush Current Peak, Surge Protection, Conductor Size, Terminal Type).

Order Code: XCBLP6630NWD
30W - Recessed Backlit Panel - 600mm x 600mm - 4000K

Dimensions

| | |
|--------|-----|
| A (mm) | 595 |
| B (mm) | 595 |
| C (mm) | 35 |

Line Drawing

