


Order Code: XCCDL3CTW

CIRCULAR CABINET LIGHT CC XCCDL - White - 3W - 3000K-4000K - Fixed output



Features

- Suitable for kitchen or wardrobe applications
- LED circular under cabinet downlight
- Can be surface or flush/recessed mounted
- Complete with 1.5m of mains, 2 core cable
- CCT [3000K/4000K] adjustable via 2-way selector switch

Construction

- Pressed steel body
- Frosted polycarbonate diffuser
- Integral driver circuitry with mains input

Technical Data

General

Luminaire Wattage (W)	3
Weight (kg)	0.17
Operating Temperature (ta °C)	-20 to 50

Light Output

Lumens (lm)	240
Efficacy (lm/W)	80

LED

CCT (K)	3000K/4000K
CRI	80
Macadam Ellipses	<5

Driver

Driver Current (mA)	120
Forward Voltage (V)	18

Electrical

Rated Input Current (A)	0.03
Power Factor (pf)	0.42
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	110
Surge Protection (kV)	0.5kV
Conductor Size (mm)	0.5
Terminal Type	2 core flex

Order Code: XCCDL3CTW

CIRCULAR CABINET LIGHT CC XCCDL - White - 3W - 3000K-4000K - Fixed output

Dimensions

C (mm)	27
Fix	48
Dia. (mm)	73

Line Drawing

