

Order Code: XCCDL3NWW
3W - Circular Under Cabinet Downlight - IP20 - 4000K - White



Features

- Suitable for kitchen or wardrobe applications
• LED circular under cabinet downlight
• Can be surface or flush/recessed mounted
• Complete with 0.5m of mains, 2 core cable
• Up to 67 lumens per watt efficacy

Construction

- Pressed steel body
• Frosted polycarbonate diffuser
• Integral driver circuitry with mains input
• Available in warm white [3000K] or neutral white [4000K]

Note: Please note dimensions relate to the 'surface' fitting [WITH TRIM]. The dimensions [WITHOUT TRIM] for recessed install are [Cut-out. 60mm] [Dia. 68mm] [C. 23mm]

Technical Data

Table with 2 main sections: General and Electrical. General includes Luminaire Wattage (W), Weight (kg), Operating Temperature (ta °C), Light Output (Lumens (lm), Efficacy (lm/W)), and LED (CCT (K), CRI, Macadam Elipses). Electrical includes Rated Input Current (A), Power Factor (pf), Input Voltage Range (VAC), Surge Protection (kV), Conductor Size (mm), and Terminal Type.

**Order Code:** XCCDL3NWW  
3W - Circular Under Cabinet Downlight - IP20 - 4000K - White

Dimensions

C (mm)	23
Cut Out (mm)	68
Dia. (mm)	74

Line Drawing

