

Order Code: XCDK5CT

4W 5-Way Decking Light Kit - CCTK Selector [3000K/4000K]



Features

- Suitable for garden decking and walkways
- Available as 5-way or 10-way kit
- Choice of 6000K or CCTK [3000K/4000K] adjustable
- Adjustment via twist and locking loom system
- Up to 38 lumens per watt efficacy

Construction

- Polished stainless steel [Grade #304] trim with polycarbonate cover
- Supplied with outdoor IP67 LED Driver



Technical Data

| General | | Electrical | |
|-------------------------------|-----------|---------------------------|----------|
| Luminaire Wattage (W) | 4 | Rated Input Current (A) | 0.04 |
| Weight (kg) | 0.30 | Power Factor (pf) | 0.46 |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 110-240V |
| Light Output | | Inrush Current Peak (A) | 35.32 |
| Lumens (lm) | 150 | Surge Protection (kV) | 2 |
| Efficacy (lm/W) | 38 | | |
| LED | | | |
| CCT (K) | 3000-4000 | | |
| CRI | >80 | | |
| Macadam Ellipses | 5.5 | | |
| Driver | | | |
| Driver Current (mA) | 660mA | | |
| Forward Voltage (V) | 12V | | |

Order Code: XCDK5CT

4W 5-Way Decking Light Kit - CCTK Selector [3000K/4000K]

Dimensions

| | |
|--------------|-------|
| A (mm) | 10025 |
| B (mm) | 1500 |
| C (mm) | 2225 |
| E (mm) | 26 |
| Cut Out (mm) | 22 |
| Dia. (mm) | 30 |

Line Drawing

