

**Order Code: XCDK5DL**

4W 5-Way Decking Light Kit - 6000K



**Features**

- Suitable for garden decking and walkways
- Available as 5-way or 10-way kit
- Choice of 6000K or CCTK [3000K/4000K] adjustable
- Adjustment via twist and locking loom system
- Up to 50 lumens per watt efficacy

**Construction**

- Polished stainless steel [Grade #304] trim with polycarbonate cover
- Supplied with outdoor IP67 LED Driver



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	4	Rated Input Current (A)	0.04
Weight (kg)	0.30	Power Factor (pf)	0.46
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	110-240V
		Inrush Current Peak (A)	26.7
		Surge Protection (kV)	2
Light Output			
Lumens (lm)	200		
Efficacy (lm/W)	50		
LED			
CCT (K)	6000		
CRI	>80		
Macadam Ellipses	5.5		
Driver			
Driver Current (mA)	420mA		
Forward Voltage (V)	12V		

**Order Code: XCDK5DL**  
4W 5-Way Decking Light Kit - 6000K

Dimensions

A (mm)	10025
B (mm)	1500
C (mm)	2225
E (mm)	26
Cut Out (mm)	22
Dia. (mm)	30

Line Drawing

