

Order Code: XCDL12NW
12W - Downlight Ultra Slim Low Profile - IP20 - 4000K



Features

- Ideal for retrofit of existing CFL Fixtures
- Suitable for general circulation areas
- Available in 6 sizes
- Edge-lit LED array with ultra slim profile
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 92 lumens per watt efficacy

Construction

- Die-cast aluminium body
- Opal polystyrene diffuser - TP[b]
- Plug and play driver
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]

3000K 4000K 6000K 30,000 HOURS 3YRS WARRANTY IP20 IK03

Technical Data

General		Electrical	
Luminaire Wattage (W)	12	Rated Input Current (A)	0.06
Weight (kg)	0.32	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	200-240
Light Output		Inrush Current Peak (A)	6.78
Lumens (lm)	1100	Surge Protection (kV)	2
Efficacy (lm/W)	92	Conductor Size (mm)	1.5
LED		Terminal Type	2 pole grip wire
CCT (K)	4000		
CRI	80		
Macadam Ellipses	4		
Driver			
Driver Current (mA)	300		
Forward Voltage (V)	28-31		

Order Code: XCDL12NW

12W - Downlight Ultra Slim Low Profile - IP20 - 4000K

Dimensions

C (mm)	25
Cut Out (mm)	156
Dia. (mm)	170

Line Drawing

