

**Order Code: XCDL12WW**

12W - Downlight Ultra Slim Low Profile - IP20 - 3000K

**Features**

- Ideal for retrofit of existing CFL Fixtures
- Suitable for general circulation areas
- Available in 6 sizes
- Edge-lit LED array with ultra slim profile
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 88 lumens per watt efficacy

**Construction**

- Die-cast aluminium body
- Opal polystyrene diffuser - TP[b]
- Plug and play driver
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]

**Technical Data****General**

Luminaire Wattage (W)	12
Weight (kg)	0.32
Operating Temperature (ta °C)	0 to 25

**Light Output**

Lumens (lm)	1050
Efficacy (lm/W)	88

**LED**

CCT (K)	3000
CRI	80
Macadam Ellipses	4

**Driver**

Driver Current (mA)	300
Forward Voltage (V)	28-31

**Electrical**

Rated Input Current (A)	0.06
Power Factor (pf)	0.9
Input Voltage Range (VAC)	200-240
Inrush Current Peak (A)	6.78
Surge Protection (kV)	2
Conductor Size (mm)	1.5
Terminal Type	2 pole grip wire

### Order Code: XCDL12WW

12W - Downlight Ultra Slim Low Profile - IP20 - 3000K

#### Dimensions

C (mm)	25
Cut Out (mm)	156
Dia. (mm)	170

#### Line Drawing

