xcite LED Lighting

Data Sheet



Order Code: XCDL12WW

12W - Downlight Ultra Slim Low Profile - IP20 - 3000K



Features

- Ideal for retrofit of existing CFL Fixtures
- Suitable for general circulation areas
- · Available in 6 sizes
- Edge-lit LED array with ultra slim profile
- 3 hours emergency maintained with compatible conversion box Emergency Kit
- Up to 88 lumens per watt efficacy

Construction

- · Die-cast aluminium body
- Opal polystyrene diffuser TP[b]
- · Plug and play driver
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]

















Technical Data

General		
Luminaire Wattage (W)	12	F
Weight (kg)	0.32	F
Operating Temperature (ta °C)		I
Light Output		
Lumens (lm)	1050	
Efficacy (lm/W)	88	
LED		'
CCT (K)	3000	
CRI	80	
Macadam Elipses	4	
Driver		
Driver Current (mA)	300	
Forward Voltage (V)	28-31	

Electrical		
Rated Input Current (A)	0.06	
Power Factor (pf)	0.9	
Input Voltage Range (VAC)	200-240	
Inrush Current Peak (A)	6.78	
Surge Protection (kV)	2	
Conductor Size (mm)	1.5	
Terminal Type	2 pole grip wire	

xcite LED Lighting

Data Sheet



Order Code: XCDL12WW

12W - Downlight Ultra Slim Low Profile - IP20 - 3000K

Dimensions

C (mm)	25
Cut Out (mm)	156
Dia. (mm)	170

Line Drawing





