# xcite LED Lighting

## **Data Sheet**



Order Code: XCDL15DL

15W - Downlight Ultra Slim Low Profile - IP20 - 6000K



#### **Features**

- Ideal for retrofit of existing CFL Fixtures
- Suitable for general circulation areas
- Available in 6 sizes
- Edge-lit LED array with ultra slim profile
- 3 hours emergency maintained with compatible conversion box **Emergency Kit**
- Up to 104 lumens per watt efficacy

### Construction

- · Die-cast aluminium body
- Opal polystyrene diffuser TP[b]
- · Plug and play driver
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]

















## **Technical Data**

General	
Luminaire Wattage (W)	15
Weight (kg)	0.43
Operating Temperature (ta °C)	0 to 25
Light Output	
Lumens (Im)	1350
Efficacy (lm/W)	104
LED	
CCT (K)	6000
CRI	80
Macadam Elipses	4
Driver	
Driver Current (mA)	350
Forward Voltage (V)	28-31

Electrical	
Rated Input Current (A)	0.07
Power Factor (pf)	0.9
Input Voltage Range (VAC)	200-240
Inrush Current Peak (A)	6.78
Surge Protection (kV)	2
Conductor Size (mm)	1.5
Terminal Type	2 pole grip wire

# xcite LED Lighting

# **Data Sheet**




Order Code: XCDL15DL

15W - Downlight Ultra Slim Low Profile - IP20 - 6000K

#### **Dimensions**

C (mm)	25
Cut Out (mm)	185
Dia. (mm)	200

### Line Drawing



Dia



