xcite LED Lighting

Data Sheet



Order Code: XCDL17DL

17W - Downlight Ultra Slim Low Profile - IP20 - 6000K



Features

- Ideal for retrofit of existing CFL Fixtures
- Suitable for general circulation areas
- · Available in 6 sizes
- Edge-lit LED array with ultra slim profile
- 3 hours emergency maintained with compatible conversion box **Emergency Kit**
- Up to 97 lumens per watt efficacy

Construction

- · Die-cast aluminium body
- Opal polystyrene diffuser TP[b]
- · Plug and play driver
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]

















Technical Data

General	
Luminaire Wattage (W)	17
Weight (kg)	0.50
Operating Temperature (ta °C)	0 to 25
Light Output	-
Lumens (Im)	1650 -
Efficacy (lm/W)	97 -
LED	-
CCT (K)	6000
CRI	80
Macadam Elipses	4
Driver	
Driver Current (mA)	450
Forward Voltage (V)	28-31

Electrical	
Rated Input Current (A)	0.08
Power Factor (pf)	0.9
Input Voltage Range (VAC)	200-240
Inrush Current Peak (A)	7.86
Surge Protection (kV)	2
Conductor Size (mm)	1.5
Terminal Type	2 pole grip wire



xcite LED Lighting

Data Sheet



Order Code: XCDL17DL

17W - Downlight Ultra Slim Low Profile - IP20 - 6000K

Dimensions

C (mm)	25
Cut Out (mm)	225
Dia. (mm)	238

Line Drawing





