

**Order Code: XCDL17DL**

17W - Downlight Ultra Slim Low Profile - IP20 - 6000K



**Features**

- Ideal for retrofit of existing CFL Fixtures
- Suitable for general circulation areas
- Available in 6 sizes
- Edge-lit LED array with ultra slim profile
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 97 lumens per watt efficacy

**Construction**

- Die-cast aluminium body
- Opal polystyrene diffuser - TP[b]
- Plug and play driver
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	17	Rated Input Current (A)	0.08
Weight (kg)	0.50	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	200-240
<b>Light Output</b>		Inrush Current Peak (A)	7.86
Lumens (lm)	1650	Surge Protection (kV)	2
Efficacy (lm/W)	97	Conductor Size (mm)	1.5
<b>LED</b>		Terminal Type	2 pole grip wire
CCT (K)	6000		
CRI	80		
Macadam Elipses	4		
<b>Driver</b>			
Driver Current (mA)	450		
Forward Voltage (V)	28-31		

**Order Code:** XCDL17DL

17W - Downlight Ultra Slim Low Profile - IP20 - 6000K

### Dimensions

C (mm)	25
Cut Out (mm)	225
Dia. (mm)	238

### Line Drawing

