

Order Code: XCDL22DL

22W - Downlight Ultra Slim Low Profile - IP20 - 6000K



Features

- Ideal for retrofit of existing CFL Fixtures
- Suitable for general circulation areas
- Available in 6 sizes
- Edge-lit LED array with ultra slim profile
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 102 lumens per watt efficacy

Construction

- Die-cast aluminium body
- Opal polystyrene diffuser - TP[b]
- Plug and play driver
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]



Technical Data

General		Electrical	
Luminaire Wattage (W)	22	Rated Input Current (A)	0.1
Weight (kg)	0.73	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	200-240
Light Output		Inrush Current Peak (A)	6.63
		Surge Protection (kV)	2
		Conductor Size (mm)	1.5
Lumens (lm)	2250	Terminal Type	2 pole grip wire
Efficacy (lm/W)	102		
LED			
CCT (K)	6000		
CRI	80		
Macadam Ellipses	4		
Driver			
Driver Current (mA)	550		
Forward Voltage (V)	28-31		

Order Code: XCDL22DL

22W - Downlight Ultra Slim Low Profile - IP20 - 6000K

Dimensions

C (mm)	25
Cut Out (mm)	280
Dia. (mm)	296

Line Drawing

