

**Order Code: XCDL4DL**

4W - Downlight Ultra Slim Low Profile - IP20 - 6000K



**Features**

- Ideal for retrofit of existing CFL Fixtures
- Suitable for general circulation areas
- Available in 6 sizes
- Edge-lit LED array with ultra slim profile
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 88 lumens per watt efficacy

**Construction**

- Die-cast aluminium body
- Opal polystyrene diffuser - TP[b]
- Plug and play driver
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]



**Technical Data**

| General                       |         | Electrical                |                  |
|-------------------------------|---------|---------------------------|------------------|
| Luminaire Wattage (W)         | 4       | Rated Input Current (A)   | 0.02             |
| Weight (kg)                   | 0.15    | Power Factor (pf)         | 0.9              |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 200-240          |
|                               |         | Inrush Current Peak (A)   | 6.84             |
|                               |         | Surge Protection (kV)     | 2                |
|                               |         | Conductor Size (mm)       | 1.5              |
|                               |         | Terminal Type             | 2 pole grip wire |
| Light Output                  |         |                           |                  |
| Lumens (lm)                   | 350     |                           |                  |
| Efficacy (lm/W)               | 88      |                           |                  |
| LED                           |         |                           |                  |
| CCT (K)                       | 6000    |                           |                  |
| CRI                           | 80      |                           |                  |
| Macadam Ellipses              | 4       |                           |                  |
| Driver                        |         |                           |                  |
| Driver Current (mA)           | 130     |                           |                  |
| Forward Voltage (V)           | 28-31   |                           |                  |

**Order Code:** XCDL4DL

4W - Downlight Ultra Slim Low Profile - IP20 - 6000K

### Dimensions

|              |    |
|--------------|----|
| C (mm)       | 25 |
| Cut Out (mm) | 72 |
| Dia. (mm)    | 90 |

### Line Drawing

