

Order Code: XCDL4NW

4W - Downlight Ultra Slim Low Profile - IP20 - 4000K

**Features**

- Ideal for retrofit of existing CFL Fixtures
- Suitable for general circulation areas
- Available in 6 sizes
- Edge-lit LED array with ultra slim profile
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 88 lumens per watt efficacy

Construction

- Die-cast aluminium body
- Opal polystyrene diffuser - TP[b]
- Plug and play driver
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]

Technical Data**General**

Luminaire Wattage (W)	4
Weight (kg)	0.15
Operating Temperature (ta °C)	0 to 25

Light Output

Lumens (lm)	350
Efficacy (lm/W)	88

LED

CCT (K)	4000
CRI	80
Macadam Ellipses	4

Driver

Driver Current (mA)	130
Forward Voltage (V)	28-31

Electrical

Rated Input Current (A)	0.02
Power Factor (pf)	0.9
Input Voltage Range (VAC)	200-240
Inrush Current Peak (A)	6.84
Surge Protection (kV)	2
Conductor Size (mm)	1.5
Terminal Type	2 pole grip wire

Order Code: XCDL4NW

4W - Downlight Ultra Slim Low Profile - IP20 - 4000K

Dimensions

C (mm)	25
Cut Out (mm)	72
Dia. (mm)	90

Line Drawing

