xcite LED Lighting

Data Sheet

EXCITE

Order Code: XCDL4WW

4W - Downlight Ultra Slim Low Profile - IP20 - 3000K



Features

- Ideal for retrofit of existing CFL Fixtures
- Suitable for general circulation areas
- · Available in 6 sizes
- Edge-lit LED array with ultra slim profile
- 3 hours emergency maintained with compatible conversion box Emergency Kit
- Up to 75 lumens per watt efficacy

Construction

- · Die-cast aluminium body
- Opal polystyrene diffuser TP[b]
- · Plug and play driver
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]

















Technical Data

General		
Luminaire Wattage (W)	4	Rated
Weight (kg)	0.15	Power
Operating Temperature (ta °C)		Input \
Light Output		Inrush
Lumens (Im)	300	Surge
Efficacy (lm/W)	75	Condu
LED		Termir
CCT (K)	3000	
CRI	80	
Macadam Elipses	4	
Driver		
Driver Current (mA)	130	
Forward Voltage (V)		

Electrical		
Rated Input Current (A)	0.02	
Power Factor (pf)	0.9	
Input Voltage Range (VAC)	200-240	
Inrush Current Peak (A)	6.84	
Surge Protection (kV)	2	
Conductor Size (mm)	1.5	
Terminal Type	2 pole grip wire	



xcite LED Lighting

Data Sheet




Order Code: XCDL4WW

4W - Downlight Ultra Slim Low Profile - IP20 - 3000K

Dimensions

C (mm)	25
Cut Out (mm)	72
Dia. (mm)	90

Line Drawing



Dia



