

Order Code: XCDLAM3ST

XCITE DROP LIGHT ST XCDLA 2W - 6500K - Fixed output - Emergency Self-test



Features

- Ideal for retrofit of existing emergency fixtures
- Suitable for escape routes and exits
- Reduced maintenance and high performance
- Supplied with LiFePO4 battery

Construction

- Surface box with suspended legend
- Polycarbonate body
- Operates in maintained and non-maintained mode
- Wire suspension [0 - 750mm]
- Supplied with EURO 4 running man legend
- Integral auto self-test for reduced maintenance, includes a disable function



Technical Data

| General | | Electrical | |
|-------------------------------|-----------|---------------------------|-------------------|
| Luminaire Wattage (W) | 2 | Rated Input Current (A) | 0.05 |
| Weight (kg) | 0.60 | Power Factor (pf) | 0.19 |
| Operating Temperature (ta °C) | 5° to 25° | Input Voltage Range (VAC) | 220 to 240 |
| | | Conductor Size (mm) | 1.5 |
| | | Terminal Type | 4 pole screw down |
| Driver | | | |
| Driver Current (mA) | 110 | | |
| Forward Voltage (V) | 2.68 | | |

Order Code: XCDLAM3ST

XCITE DROP LIGHT ST XCDLA 2W - 6500K - Fixed output - Emergency Self-test

Dimensions

| | |
|--------|------|
| A (mm) | 340 |
| B (mm) | 45 |
| C (mm) | 1000 |

Line Drawing

