xcite LED Lighting

Data Sheet



Order Code: XCDLAM3ST

XCITE DROP LIGHT ST XCDLA 2W - 6500K - Fixed output - Emergency Self-test



Features

- Ideal for retrofit of existing emergency fixtures
- Suitable for escape routes and exits
- Reduced maintenance and high performance
- Supplied with LiFePO4 battery

Construction

- Surface box with suspended legend
- Polycarbonate body
- Operates in maintained and non-maintained mode
- Wire suspension [0 750mm]
- Supplied with EURO 4 running man legend
- Integral auto self-test for reduced maintenance













Technical Data

General	Electrical
/) 2 Rated Inp	t Current (A) 0.05
0.60 Power Fac	tor (pf) 0.19
re (ta °C) 5° to 25° Input Volta	ge Range (VAC) 220 to 240
Driver Conducto	Size (mm) 1.5
Terminal 110	ype 4 pole screw down
2.68	
0.60 Power Factor (ta °C) 5° to 25° Input Volta Conductor Driver Terminal	tor (pf) 0. ge Range (VAC) 220 to 2 Size (mm)



xcite LED Lighting

Data Sheet



Order Code: XCDLAM3ST

XCITE DROP LIGHT ST XCDLA 2W - 6500K - Fixed output - Emergency Self-test

Dimensions

A (mm)	340
B (mm)	45
C (mm)	1000

Line Drawing



