

**Order Code: XCDLAM3STEU3**

XCITE DROP LIGHT ST XCDLA 2W - 6500K - Fixed output - Emergency Self-test



**Features**

- Ideal for retrofit of existing emergency fixtures
- Suitable for escape routes and exits
- Reduced maintenance and high performance
- Supplied with LiFePO4 battery

**Construction**

- Surface box with suspended legend
- Polycarbonate body
- Operates in maintained and non-maintained mode
- Wire suspension [0 - 750mm]
- Supplied with EURO 4 running man legend
- Integral auto self-test for reduced maintenance, includes a disable function



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	2	Rated Input Current (A)	0.05
Weight (kg)	0.60	Power Factor (pf)	0.19
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
		Conductor Size (mm)	1.5
		Terminal Type	4 pole screw down
Driver			
Driver Current (mA)	110		
Forward Voltage (V)	2.68		

**Order Code:** XCDLAM3STEU3

XCITE DROP LIGHT ST XCDLA 2W - 6500K - Fixed output - Emergency Self-test

### Dimensions

A (mm)	340
B (mm)	45
C (mm)	1000

### Line Drawing

