

Order Code: XCDLUCT

10-16W - Universal Downlight - CCTK Selector [3000K/4000K/6000K] - White



Features

- Universal downlight for retrofitting into wide range of cut-outs
- Adjustable bracket allows retrofitting into existing cut-out of 65mm to 205mm
- CCT adjustable via selector switch [3000K/4000K/6000K]
- A choice of wattages selectable via switch [10W, 13W, 16W]
- Ideal solution when cut-out and colour temperature requirements are not known
- Up to 90 lumens per watt efficacy

Construction

- Polycarbonate body
- Opal polystyrene diffuser
- Integral driver



Technical Data

General		Electrical	
Luminaire Wattage (W)	10-16	Rated Input Current (A)	0.18
Weight (kg)	0.36	Power Factor (pf)	0.9
Light Output		Input Voltage Range (VAC)	85-65
Lumens (lm)	900 to 1500	Inrush Current Peak (A)	6.8
Efficacy (lm/W)	90	Surge Protection (kV)	0.5
LED			
CCT (K)	3000K/4000K/6000K		
Driver			
Driver Current (mA)	210		
Forward Voltage (V)	65 to 78		

Order Code: XCDLUCT

10-16W - Universal Downlight - CCTK Selector [3000K/4000K/6000K] - White

Dimensions

C (mm)	17
Cut Out (mm)	65-205
Dia. (mm)	235

Line Drawing

