

Order Code: XCDLUCT

10-16W - Universal Downlight - CCTK Selector [3000K/4000K/6000K] - White



Features

- Universal downlight for retrofitting into wide range of cut-outs
- Adjustable bracket allows retrofitting into existing cut-out of 65mm to 205mm
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- A choice of wattages selectable via switch [10W, 13W, 16W]
- Ideal solution when cut-out and colour temperature requirements are not known
- Up to 90 lumens per watt efficacy

Construction

- Polycarbonate body
- Opal polystyrene diffuser
- Integral driver

Technical Data

General

Luminaire Wattage (W)	10-16
Weight (kg)	0.36

Light Output

Lumens (lm)	900 to 1500
Efficacy (lm/W)	90

Electrical

Rated Input Current (A)	0.18
Power Factor (pf)	0.9
Input Voltage Range (VAC)	85-265
Inrush Current Peak (A)	6.8
Surge Protection (kV)	0.5

LED

CCT (K)	TRI-COLOUR
---------	------------

Driver

Driver Current (mA)	210
Forward Voltage (V)	65 to 78

Order Code: XCDLUCT

10-16W - Universal Downlight - CCTK Selector [3000K/4000K/6000K] - White

Dimensions

C (mm)	17
Cut Out (mm)	65-205
Dia. (mm)	235

Line Drawing

