xcite LED Lighting

Data Sheet



Order Code: XCDLUCT

10-16W - Universal Downlight - CCTK Selector [3000K/4000K/6000K] - White



Features

- Universal downlight for retrofitting into wide range of cut-outs
- Adjustable bracket allows retrofitting into existing cut-out of 65mm to 205mm
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- A choice of wattages selectable via switch [10W, 13W, 16W]
- Ideal solution when cut-out and colour temperature requirements are not known
- Up to 90 lumens per watt efficacy

Construction

- Polycarbonate body
- Opal polystyrene diffuser
- Integral driver













Technical Data

Toolinga Data				
General		Electrical		
Luminaire Wattage (W)	10-16	Rated Input Current (A)	0.18	
Weight (kg)	0.36	Power Factor (pf)	0.9	
Light Output Lumens (lm)		Input Voltage Range (VAC)	85-65	
	900-1500	Inrush Current Peak (A)	6.8	
Efficacy (lm/W)	90	Surge Protection (kV)	0.5	
LED				
CCT (K)	TRI-COLOUR			
Driver				
Driver Current (mA)	210			
Forward Voltage (V)	65 to 78			



xcite LED Lighting

Data Sheet



Order Code: XCDLUCT

10-16W - Universal Downlight - CCTK Selector [3000K/4000K/6000K] - White

Dimensions

C (mm)	17
Cut Out (mm)	65-205
Dia. (mm)	235

Line Drawing



