

Order Code: XCDLWP5NWB

5W - Downlight WP - 4000K - Black

**Features**

- Suitable for exterior canopy areas and soffits
- Available in white, black or anthracite grey trim finish
- Phase cut dimming as standard

Construction

- IP65 rated from above and below, with sealed pre-wired lead [1.5M]
- Die-cast aluminium body with integral driver
- Robust construction with corrosion resistant marine grade paint
- Available in warm white [3000K] or neutral white [4000K]

Technical Data**General**

| | |
|-------------------------------|-----------|
| Luminaire Wattage (W) | 5 |
| Operating Temperature (ta °C) | -20 to 40 |

Light Output

| | |
|-----------------|-----|
| Lumens (lm) | 500 |
| Efficacy (lm/W) | 100 |

LED

| | |
|------------------|------|
| CCT (K) | 4000 |
| CRI | 80 |
| Macadam Ellipses | 5 |

Driver

| | |
|---------------------|---------|
| Driver Current (mA) | 25 |
| Forward Voltage (V) | 220-240 |

Electrical

| | |
|---------------------------|-------------------|
| Rated Input Current (A) | 0.025 |
| Power Factor (pf) | 0.9 |
| Input Voltage Range (VAC) | 220-240 |
| Inrush Current Peak (A) | 0.7 |
| Surge Protection (kV) | 1 |
| Conductor Size (mm) | 0.5 to 2.5 |
| Terminal Type | 2-pole screw down |

Order Code: XCDLWP5NWB

5W - Downlight WP - 4000K - Black

Dimensions

| | |
|--------------|----|
| C (mm) | 45 |
| Cut Out (mm) | 66 |
| Dia. (mm) | 90 |

Line Drawing

