

**Order Code: XCDLWP5NWB**

5W - Downlight WP - 4000K - Black

**Features**

- Suitable for exterior canopy areas and soffits
- Available in white, black or anthracite grey trim finish
- Phase cut dimming as standard

**Construction**

- IP65 rated from above and below, with sealed pre-wired lead [1.5M]
- Die-cast aluminium body with integral driver
- Robust construction with corrosion resistant marine grade paint
- Available in warm white [3000K] or neutral white [4000K]



**Technical Data**

**General**

Luminaire Wattage (W)	5
Operating Temperature (ta °C)	-20 to 40

**Light Output**

Lumens (lm)	500
Efficacy (lm/W)	100

**LED**

CCT (K)	4000
CRI	80
Macadam Elipses	5

**Driver**

Driver Current (mA)	25
Forward Voltage (V)	220-240

**Electrical**

Rated Input Current (A)	0.025
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	0.7
Surge Protection (kV)	1
Conductor Size (mm)	0.5 to 2.5
Terminal Type	2-pole screw down

**Order Code:** XCDLWP5NWB  
5W - Downlight WP - 4000K - Black

### Dimensions

C (mm)	45
Cut Out (mm)	66
Dia. (mm)	90

### Line Drawing

