xcite LED Lighting

Data Sheet



Order Code: XCDLWP5WWG

5W - Downlight WP - 3000K - Anthracite Grey



Features

- Suitable for exterior canopy areas and soffits
- · Available in white, black or anthracite grey trim finish
- Phase cut dimming as standard

Construction

- IP65 rated from above and below, with sealed pre-wired lead [1.5M]
- Die-cast aluminium body with integral driver
- Robust construction with corrosion resistant marine grade paint
- Available in warm white [3000K] or neutral white [4000K]

















Technical Data

General		Electrical	
Luminaire Wattage (W)	5	Rated Input Current (A)	0.025
Operating Temperature (ta °C)	-20 to 40	Power Factor (pf)	0.9
Light Output Lumens (Im)		Input Voltage Range (VAC)	220-240
	500	Inrush Current Peak (A)	0.7
Efficacy (Im/W)	100	Surge Protection (kV)	1
Lineacy (iiivv)		Conductor Size (mm)	0.5 to 2.5
LED		Terminal Type	2-pole screw down
CCT (K)	3000		
CRI	80		
Macadam Elipses	5		
Driver			
Driver Current (mA)	25		
Forward Voltage (V)	220-240		



xcite LED Lighting

Data Sheet



Order Code: XCDLWP5WWG

5W - Downlight WP - 3000K - Anthracite Grey

Dimensions

C (mm)	45
Cut Out (mm)	66
Dia. (mm)	90

Line Drawing



