xcite LED Lighting

Data Sheet



Order Code: XCDR5

6W - Compact Bulkhead with Opal Diffuser - 4000K





- · Ideal for retrofit of existing GLS fixtures
- Suitable for bathrooms or storerooms
- Low energy LED module for reduced running costs
- Up to 83 lumens per watt efficacy

Construction

- Polycarbonate body
- High quality polycarbonate construction
- Opal diffuser
- Supplied as standard with neutral white [4000K] LED













Technical Data

Technical Data				
General		Electrical		
Luminaire Wattage (W)	6	Rated Input Current (A)	0.048	
Weight (kg)	0.33	Power Factor (pf)	0.5	
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240	
Light Output Lumens (Im)		Inrush Current Peak (A)	25	
	500	Surge Protection (kV)	1	
Efficacy (lm/W)	83	Conductor Size (mm)	2.5	
Lineacy (III/VV)		Terminal Type	3 pole piano key	
LED				
CCT (K)	4000			
CRI	80			
Macadam Elipses	4			
Driver				
Driver Current (mA)	350			
Forward Voltage (V)	11.2 to 13.6			



xcite LED Lighting

Data Sheet



Order Code: XCDR5

6W - Compact Bulkhead with Opal Diffuser - 4000K

Dimensions

C (mm)	69
Dia. (mm)	160

Line Drawing

