

Order Code: XCDR5
6W - Compact Bulkhead with Opal Diffuser - 4000K



- Features
- Ideal for retrofit of existing GLS fixtures
  - Suitable for bathrooms or storerooms
  - Low energy LED module for reduced running costs
  - Up to 83 lumens per watt efficacy
- Construction
- Polycarbonate body
  - High quality polycarbonate construction
  - Opal diffuser
  - Supplied as standard with neutral white [4000K] LED

Technical Data

General		Electrical	
Luminaire Wattage (W)	6	Rated Input Current (A)	0.048
Weight (kg)	0.33	Power Factor (pf)	0.5
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
Light Output		Inrush Current Peak (A)	25
Lumens (lm)	500	Surge Protection (kV)	1
Efficacy (lm/W)	83	Conductor Size (mm)	2.5
LED		Terminal Type	3 pole piano key
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		
Driver			
Driver Current (mA)	350		
Forward Voltage (V)	11.2 to 13.6		

**Order Code:** XCDR5  
6W - Compact Bulkhead with Opal Diffuser - 4000K

Dimensions

C (mm)	69
Dia. (mm)	160

Line Drawing

