

Order Code: XCDR5

6W - Compact Bulkhead with Opal Diffuser - 4000K



Features

- Ideal for retrofit of existing GLS fixtures
- Suitable for bathrooms or storerooms
- Low energy LED module for reduced running costs
- Up to 83 lumens per watt efficacy

Construction

- Polycarbonate body
- High quality polycarbonate construction
- Opal diffuser
- Supplied as standard with neutral white [4000K] LED



Technical Data

General		Electrical	
Luminaire Wattage (W)	6	Rated Input Current (A)	0.048
Weight (kg)	0.33	Power Factor (pf)	0.5
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
		Inrush Current Peak (A)	25
		Surge Protection (kV)	1
		Conductor Size (mm)	2.5
		Terminal Type	3 pole piano key
Light Output			
Lumens (lm)	500		
Efficacy (lm/W)	83		
LED			
CCT (K)	4000		
CRI	80		
Macadam Ellipses	4		
Driver			
Driver Current (mA)	350		
Forward Voltage (V)	11.2 to 13.6		

Order Code: XCDR5

6W - Compact Bulkhead with Opal Diffuser - 4000K

Dimensions

C (mm)	69
Dia. (mm)	160

Line Drawing

