

**Order Code:** XCDRV24150

150W - 24V LED Strip Driver - Non-Dimmable

### Features

- 24V LED Driver for XCITE LED Strip Reels
- Short circuit and overload protection
- Fixed output models available [Non-Dimmable]
- Dimmable model available



### Technical Data

| General                       |              | Electrical                |           |
|-------------------------------|--------------|---------------------------|-----------|
| Luminaire Wattage (W)         | 150          | Rated Input Current (A)   | 0.6       |
| Weight (kg)                   | 0.30         | Power Factor (pf)         | 0.98      |
| Operating Temperature (ta °C) | -20° to 45°  | Input Voltage Range (VAC) | 220 - 240 |
|                               |              | Inrush Current Peak (A)   | 60        |
|                               |              | Surge Protection (kV)     | 1         |
|                               |              | Conductor Size (mm)       | 0.5-2.5   |
|                               |              | Terminal Type             | SCREW     |
| Driver                        |              |                           |           |
| Driver Current (mA)           | 0 - 4.16 max |                           |           |
| Forward Voltage (V)           | 24           |                           |           |

**Order Code:** XCDRV24150

150W - 24V LED Strip Driver - Non-Dimmable

### Dimensions

|        |     |
|--------|-----|
| A (mm) | 180 |
| B (mm) | 63  |
| C (mm) | 30  |

### Line Drawing

