xcite LED Lighting

Data Sheet



Order Code: XCEBANM3STEU3

XCITE EXIT BOX ST XCEBA 2W - 6500K - Fixed output - non-maintainted Emergency Self-test



Features

- Ideal for replacement of linear fluorescent fixtures
- Suitable for escape routes and exits
- 20mm conduit top and rear cable entries BESA for wall fix
- Reduced maintenance and high performance
- EURO 1, 2 and 3 running man legend also available [sold separately]
- Integral auto self-test for reduced maintenance

Construction

- Steel body
- Maintained or non-maintained available
- Supplied with EURO 4 running man legend
- Supplied with LiFePO4 battery













Technical Data

| General | | Electrical | |
|-------------------------------|-----------|---------------------------|------------------|
| Luminaire Wattage (W) | 2 | Rated Input Current (A) | 0.05 |
| Weight (kg) | 1.24 | Power Factor (pf) | 0.17 |
| Operating Temperature (ta °C) | 5° to 25° | Input Voltage Range (VAC) | 220 to 240 |
| Driver Driver Current (mA) | | Conductor Size (mm) | 1.5 |
| | 340 | Terminal Type | 3 pole push down |
| Forward Voltage (V) | 2.49 | | |



xcite LED Lighting

Data Sheet



Order Code: XCEBANM3STEU3

XCITE EXIT BOX ST XCEBA 2W - 6500K - Fixed output - non-maintainted Emergency Self-test

Dimensions

| A (mm) | 392 |
|--------|-----|
| B (mm) | 190 |
| C (mm) | 60 |

Line Drawing



