# xcite LED Lighting

## **Data Sheet**



0.051 0.4 220-240 1.5

4 pole screw down

Order Code: XCEBM3STEU3

4W - Fixed output - Emergency Self-test - 6500K



### **Features**

- Ideal for replacement of linear fluorescent fixtures
- Suitable for escape routes and exits
- 20mm conduit top and rear cable entries BESA for wall fix
- Reduced maintenance and high performance
- EURO 1, 2 and 3 running man legend also available [sold separately]

#### Construction

- Steel body
- Maintained or non-maintained available
- Supplied with EURO 4 running man legend
- Integral auto self-test for reduced maintenance













## **Technical Data**

General			Electrical
Luminaire Wattage (W)	4	Rated Input Current (A)	
Weight (kg)	1.55	Power Factor (pf)	
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	
LED		Conductor Size (mm)	
CCT (K)	6500	Terminal Type	
CRI	70		
Driver			
Driver Current (mA)	340		
Forward Voltage (V)	2.8		



# xcite LED Lighting

# **Data Sheet**



### Order Code: XCEBM3STEU3

4W - Fixed output - Emergency Self-test - 6500K

### **Dimensions**

A (mm)	392
B (mm)	190
C (mm)	60

### Line Drawing



