xcite LED Lighting
Data Sheet

Order Code: XCEBNM3

1W - Emergency Exit Box with Arrow Up Legend - 3hrs Non-Maintained Emergency



Features

- Ideal for replacement of linear fluorescent fixtures
- Suitable for escape routes and exits
- 20mm conduit side and rear cable entries BESA for wall fix
- Reduced maintenance and high performance

Construction

- Steel body
- Maintained or non-maintained available
- Supplied with EURO 4 running man legend

50,000 HOURS | 3YRS WARRANTY | IP20 | IK06 | M3 | NM3

Technical Data

General

Luminaire Wattage (W)	1
Weight (kg)	1.39
Operating Temperature (ta °C)	5 to 25

LED

CCT (K)	6500
CRI	60

Driver

Driver Current (mA)	340
Forward Voltage (V)	2.8

Electrical

Power Factor (pf)	0.19
Input Voltage Range (VAC)	220-240
Surge Protection (kV)	1
Conductor Size (mm)	1.5
Terminal Type	Piano Key

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

Order Code: XCEBNM3

1W - Emergency Exit Box with Arrow Up Legend - 3hrs Non-Maintained Emergency

Dimensions

Length (mm)	392
Width (mm)	190
Depth (mm)	60

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk