xcite LED Lighting
Data Sheet

Order Code: XCEDL1NM3

1W - Emergency Downlight - 3hrs Non-Maintained Emergency



Features

- Suitable for open areas and escape routes
- Virtually service free emergency lighting
- Easy to install with simple connection wiring
- Very low energy consumption - 1W

Construction

- Polycarbonate body
- Operates in non-maintained mode
- Separate high quality LED driver
- Internal mains connection
- Supplied as standard with daylight [6000K] LED

6000K | 50,000 HOURS | 3YRS WARRANTY | IP20 | IK06 | NM3

Technical Data

General

Luminaire Wattage (W)	1
Weight (kg)	0.36
Operating Temperature (ta °C)	5 to 25

LED

CCT (K)	6500
CRI	70

Emergency

Emergency Lumen Operating	120
Emergency Wattage (W)	1

Electrical

Rated Input Current (A)	0.035
Power Factor (pf)	0.19
Input Voltage Range (VAC)	220-240
Surge Protection (kV)	1
Conductor Size (mm)	1.5
Terminal Type	3 pole screw down

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

Order Code: XCEDL1NM3

1W - Emergency Downlight - 3hrs Non-Maintained Emergency

Dimensions

Height (mm)	57
Cut Out (mm)	50
Dia. (mm)	60

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk