# xcite LED Lighting

## **Data Sheet**



Order Code: XCEDL1NM3C

1W - Emergency Downlight - 3hrs Non-Maintained Emergency - Corridor Version



#### **Features**

- Suitable for open areas and escape routes
- Virtually service free emergency lighting
- · Easy to install with simple connection wiring
- Very low energy consumption 1W

#### Construction

- Polycarbonate body
- · Operates in non-maintained mode
- · Separate high quality LED driver
- Internal mains connection
- Supplied as standard with daylight [6000K] LED





Emergency Wattage (W)











General		Electrical	
Luminaire Wattage (W)	1	Rated Input Current (A)	0.035
Weight (kg)	0.37	Power Factor (pf)	0.19
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
LED	6500	Surge Protection (kV)	1
CCT (K)		Conductor Size (mm)	1.5
CRI	70	Terminal Type	3 pole screw down
Emergency			
Emergency Lumen Operating	105		



# xcite LED Lighting

## **Data Sheet**



### Order Code: XCEDL1NM3C

1W - Emergency Downlight - 3hrs Non-Maintained Emergency - Corridor Version

### **Dimensions**

C (mm)	57
Cut Out (mm)	50
Dia. (mm)	60

### Line Drawing



