

**Order Code: XCEDL1NM3C**

1W - Emergency Downlight - 3hrs Non-Maintained Emergency - Corridor Version

**Features**

- Suitable for open areas and escape routes
- Virtually service free emergency lighting
- Easy to install with simple connection wiring
- Very low energy consumption - 1W

**Construction**

- Polycarbonate body
- Operates in non-maintained mode
- Separate high quality LED driver
- Internal mains connection
- Supplied as standard with daylight [6000K] LED



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	1	Rated Input Current (A)	0.035
Weight (kg)	0.37	Power Factor (pf)	0.19
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
		Surge Protection (kV)	1
		Conductor Size (mm)	1.5
		Terminal Type	3 pole screw down
LED			
CCT (K)	6500		
CRI	70		
Emergency			
Emergency Lumen Operating	105		
Emergency Wattage (W)	1		

**Order Code:** XCEDL1NM3C

1W - Emergency Downlight - 3hrs Non-Maintained Emergency - Corridor Version

### Dimensions

C (mm)	57
Cut Out (mm)	50
Dia. (mm)	60

### Line Drawing

