

Order Code: XCEDL1NM3C

1W - Emergency Downlight - 3hrs Non-Maintained Emergency - Corridor Version

**Features**

- Suitable for open areas and escape routes
- Virtually service free emergency lighting
- Easy to install with simple connection wiring
- Very low energy consumption - 1W

Construction

- Polycarbonate body
- Operates in non-maintained mode
- Separate high quality LED driver
- Internal mains connection
- Supplied as standard with daylight [6000K] LED

Technical Data**General**

Luminaire Wattage (W)	1
Weight (kg)	0.37
Operating Temperature (ta °C)	5 to 25

Electrical

CCT (K)	6500	Rated Input Current (A)	0.035
Weight (kg)	0.37	Power Factor (pf)	0.19
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
LED		Surge Protection (kV)	1
CRI	70	Conductor Size (mm)	1.5
		Terminal Type	3 pole screw down

Emergency

Emergency Lumen Operating	105
Emergency Wattage (W)	1

Order Code: XCEDL1NM3C

1W - Emergency Downlight - 3hrs Non-Maintained Emergency - Corridor Version

Dimensions

C (mm)	57
Cut Out (mm)	50
Dia. (mm)	60

Line Drawing

