

**Order Code: XCEDL1NM3ST**

1W - Fixed output - Non-maintained Emergency Self-test - 6500K

**Features**

- Suitable for open areas and escape routes
- Virtually service free emergency lighting
- Easy to install with simple connection wiring

**Construction**

- Polycarbonate body
- Very low energy consumption - 1W
- Separate high quality LED driver
- Operates in non-maintained mode
- Internal mains connection
- Integral auto self-test for reduced maintenance, includes a disable function

**Technical Data****General**

Luminaire Wattage (W)	1
Weight (kg)	0.36
Operating Temperature (ta °C)	5 to 25

**Electrical**

CCT (K)	6500	Rated Input Current (A)	0.035
Weight (kg)	0.36	Power Factor (pf)	0.19
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
		Conductor Size (mm)	1.5
		Terminal Type	3 pole screw down

**LED**

CCT (K)	6500
CRI	70

**Emergency**

Emergency Lumen Operating	140
Emergency Wattage (W)	1

**Order Code: XCEDL1NM3ST**

1W - Fixed output - Non-maintained Emergency Self-test - 6500K

## Dimensions

C (mm)	57
Cut Out (mm)	50
Dia. (mm)	60

## Line Drawing

