xcite LED Lighting

Data Sheet



0.05

1.5

220 to 240

4 pole piano key

Order Code: XCEMBAM3ST

XCITE EM BULKHEAD ST XCEMBA 3W - 6500K - Fixed output - Emergency Self-test



Features

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries for wall or ceiling fix
- Semi recessed bezel available
- Reduced maintenance and high performance
- Supplied with LiFePO4 battery

Construction

- · Polycarbonate body and diffuser
- Maintained or non-maintained available
- · Supplied with self adhesive universal legend
- Supplied as standard with daylight [6500K] LED
- Integral auto self-test for reduced maintenance













Technical Data

General		Electrical
Luminaire Wattage (W)	3	Rated Input Current (A)
Weight (kg)	0.51	Power Factor (pf)
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)
		Conductor Size (mm)
Light Output Lumens (Im)	300	Terminal Type
Efficacy (lm/W)	96	
LED		
CRI	70	
Macadam Elipses	2.1	
Driver		
Driver Current (mA)	360	
Forward Voltage (V)	3.4	
Emergency		
Emergency Lumen Operating	190	
Emergency Wattage (W)	3	



xcite LED Lighting

Data Sheet



Order Code: XCEMBAM3ST

XCITE EM BULKHEAD ST XCEMBA 3W - 6500K - Fixed output - Emergency Self-test

Dimensions

A (mm)	352
B (mm)	110
C (mm)	65

Line Drawing



